

Fork Mounted Magnet

Model - IFMM



Description

A simple, but effective, method of clearing factory floors, car parks and goods yards of unwanted steel debris that could otherwise present a hazard to pneumatic tyres and operatives alike.

Model	Width (mm)	Weight (kg)	C of G (mm)	LLC (mm)
IFMM-1220	1200	52	55	N/A
IFMM-1800	1800	78	55	N/A

Standard Features

- Facility to hang from the Fork Mounted Sweeper
- Polished stainless-steel finish
- Maximum fork section 150 x 60 mm at 683 mm centres
- Zinc plated twist screws for safe attachment to truck

Optional Features

- Stainless steel scraper



TECHNICAL FILE
OPERATION, MAINTENANCE, & HEALTH AND SAFETY INSTRUCTIONS
MODEL: FORK MOUNTED MAGNET

Operation

1. Position forks to desired distance apart.
2. Drive forks into the fork pockets above the magnet.
3. Tighten the thumbscrew retention on to the forks ensuring they are adequately tightened.
4. The attachment is now ready for use.
5. Position the magnet 75/100mm from level floor and drive at the appropriate speed to suit the type of waste and terrain for effective collection.
6. When finished, raise the magnet to a workable height and scrape the magnet to remove collected product from the base into a receptacle.

Maintenance

1. The magnet should be inspected weekly for general condition with particular attention paid to:
 - A – All weld points
 - B – Wear and distortion of thumbscrew attachments
2. Damage or failure must be reported and rectified immediately prior to re-use.
3. This product is certified for six (6) months from the date of manufacture after which it is the customer's responsibility to have the product re-tested at an approved testing facility or inspected and logged in a register by a competent person as advised by the HSE.

Health and Safety

1. The manager of the department or section where the attachment is to be used must be responsible for ensuring the operators are fully conversant with the attachment, its operation, maintenance and that the thumbscrews are fitted correctly.
2. Ensure both the truck and attachments are capable of handling the intended load and its contents.
3. Ensure the shackle pin is adequately tightened before each use.
4. Ensure the thumb screws are not tightened onto taper of blade.
5. On removal of the magnets collections, please be aware of sharp steel and remove risk by wearing safety gloves.

The Operator should ensure that the above product is used for the purpose that it has been designed, tested and intended to do and no deviation to this occurs. If in doubt, consult your fork truck dealer or approved attachment supplier.