



Marlow® DATASHEET

DYNAMIC CLIMBING ROPES

A combination of good handling, abrasion resistance and outstanding dynamic and energy absorption performance make Marlow Dynamic Climbing Ropes ideal for Cows Tails, climbing and safety and back up lines when abseiling or work positioning.



PERFORMANCE

SINGLE ROPES	9.1mm	10.5mm	11mm
Rope Type	Single	Single	Single
Weight (g/m)	52	67	77
No. falls	5	10	15
Impact Force	7.3kN	7,7kN	7.7kN
Dynamic Elongation	32%	33%	33%
Static Elongation	8.5	4.6%	4.4%
Sheath Slippage	0	0	0
Certification	EN 892	EN 892	EN 892

CE Certification issued by SGS FIMKO CE0598

Key Specifications:

Application:	Climbing, Safety line, back up line, fall arrest, Cows Tails
Material:	Polyamid (Nylon)
Construction:	40 or 48 plait braided cover Multiple twisted core

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com



Certificate Number 315
ISO 9001
ISO 14001

www.marlowropes.com

Disclaimer
Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.